Songman®

# VV\_HUNTER®

**GAMING** 

**2022 CATALOGUE** 









Dongguan Songman Technology Company Limited is one of the most professional manufacturer and supplier of gaming products, located in Dongguan city, since 2009. We offer OEM business service for our good clients.

With more than ten years development, we have rich experience in researching, designing and manufacturing gaming products, especially for gaming headsets, we also applied for design patent for our main products.

Focus on unique research and design, we keep releasing newest unique design products to fulfill markets' requirement.

Compliance with BSCI and ISO 9001:2015, we have the completely management system from product design, tooling processing, hardware stamping, molding injection, assembling and packing. We also make one hundred percent full inspection before packing and shipment to ensure quality.

Applies automatic wire drawing machine, automatic high-speed hardware stamping machine, automatic injection molding machine, several assembly and packing lines, we can achieve daily output of more than ten thousand sets.

Today our products are selling not only in domestic market, but also sold to other countries in North and south America, Europe, Middle East and Asia.

As the reputable manufacturer and reliable supplier, we also try our best to supply the best business service, such as delivering the goods on time, the satisfied after-sales service.

Please don't hesitate to contact us for our good business cooperation.



### CE/ROHS/FCC/Ca65 Certificates



Gaming Headsets CE



Gaming Mouses CE



Gaming Keyboards RoHS



Gaming Headsets ROHS



Gaming Mouses RoHS



The state of the Threstopy Co., 165

Werline and the Threstopy Co., 165

Werline and the State of Threstopy Co., 165

Werline and the State of Threstopy Co., 165

Werline and the State of Threstopy Co., 165

Applicate to the State of Threstopy Co., 165

Manufacture of Threstopy Co., 165

Manufac

Gaming Headsets FCC



Gaming Keyboards CE



BSCI

ISO9001: 2015

MIC arm up / down to turn off/on MIC 2 circle LED lights





G800

#### Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz













#### Half-hidden light design

Noise cancelling microphone Volume control Extended durability nylon cord





**G610** 



Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

7.1 Channel Built-In Sound Card











Noise cancelling microphone Volume control

Extended durability nylon cord Auto-adjusting metal headband





**G900** 

#### Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

7.1 Channel Built-In Sound Card













### 2.4G & 5.8G Wireless+ RGB light+Bluetooth

Fashion Model Design Perfect Sound output

High-end Tire-Style earpads

Long time playing Compatiable with PS4. PC. Switch











#### Transmitter

## **G810W**

#### Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Operating voltage: 3.3-4.2V Operating current: 50mA Battery capacity: 500mAh Play time: 8hrs Charging time: 2.5hrs Freq.range: 2.400-5.800Ghz SNR: 75dB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

#### Microphone

Operating voltage: 5V Operating current: 40mA Freq.range: 2.400-2.480GHz Operating distance: ≥10M, 360° Receive sensitivity: -85dB













Big metal headband **Big-earpad for NC function** 











G810



Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz











### 2.4G & 5.8G Wireless+Bluetooth



### **G700W**







#### Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Operating voltage: 3.3-4.2V Operating current: 50mA Battery capacity: 500mAh Play time: 8hrs Charging time: 2.5hrs Freq.range: 2.400-5.800Ghz SNR: 75dB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

#### Microphone

Operating voltage: 5V Operating current: 40mA Freq.range: 2.400-2.480GHz Operating distance: ≥10M, 360° Receive sensitivity: -85dB











Noise cancelling microphone Volume control Extended durability nylon cord



**G700** 





#### Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz













Noise cancelling microphone Volume control





**G780** 

#### Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz















Noise cancelling microphone Volume control Extended durability nylon cord





**G790** 

#### Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz











#### **Detachable Microphone**

Noise cancelling microphone Volume control Extended durability nylon cord Auto-adjusting metal headband





**G650** 



Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz













Noise cancelling microphone Volume control Extended durability nylon cord





**G750** 



Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

### 7.1 Channel Built-In Sound Card

### Speaker Drivers Dimensions: 50mm

Impedance: 32Ω
Sensitivity: 105dB±3dB
Freq.Response: 20-20KHz
Max.Input power: 100mW
Cord length: 2.1M
PC Plug type: 3.5mm x 2 + USB
7.1 Plug type: 1 x USB













#### 9 in 1 LED lights:

RGB rainbow + RGB flow + 7 colors in one headset LED MODES:

Switch RGB rainbow to RGB flow to 7 colors on button





**G600** 







#### Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz











#### 9 in 1 LED lights:

RGB rainbow + RGB flow + 7 colors in one headset LED MODES:

Switch RGB rainbow to RGB flow to 7 colors on button





**G500** 

#### Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz















Noise cancelling microphone Volume control Extended durability nylon cord





**G300** 

#### Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freg.Response: 50-10KHz













#### 9 in 1 LED lights:

RGB rainbow + RGB flow + 7 colors in one headset LED MODES:

Switch RGB rainbow to RGB flow to 7 colors on button





**G550** 

#### Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz



















Noise cancelling microphone Volume control Extended durability nylon cord Auto-adjusting metal headband





**G200** 

#### Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freg.Response: 50-10KHz















G100

#### Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

#### Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freg.Response: 50-10KHz

















## **V100**

Keys: 104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













## **V200**

Keys: 104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer







### 3 Modes:

### 2.4G+Bluetooth+Detachable Wired

Stylish design
Double colors injection
Key stoke 2.0MM
50 million switch life span
Backlights for key caps and gaps











# V300/V300W

Keys: 104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













## K310

Keys: 87
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













**K311** 



Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













## **K320**

Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RCB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer







### 3 Modes:

### 2.4G+Bluetooth+Detachable Wired

Stylish design
Double colors injection
Key stoke 2.0MM
50 million switch life span
Backlights for key caps and gaps











## K321/K321W

Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













## **K330**

Keys:61
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















Keys:87
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















## K340

Keys:61
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















## K350

Keys:87
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















Keys:87
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















## K360

Keys:68
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













## **K370**

Keys:87
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













## K371

Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer









### Specifications

Sensor: Optical,PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m













### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m













### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m













### Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m









### Gaming here Happy here!

#### **ADD**

Building E, 2nd Rd., Fulong 2nd Industrial Park, Shipai Town, Dongguan City, Guangdong Province, China 523 349

#### **EMAIL**

sales@songman-china.com

#### **TEL**

+86-769-8278 0755

#### **FAX**

+86-769-8278 0756

#### Dongguan Songman Technology Co., LTD.

www.songman-china.com www.vvhunter.com



Scan Wechat